Unified Battery Charger 3 Bay Rack Set (with AC adapter) for CISCO 7926G/7925G/7925G-EX Unified Wireless IP Phone

Product ID:CI925U3B| Compatibility: zBattery and Cisco 7926G/7925G/7925G-EX Wireless IP Phone Battery

zAdapter® CI925U3B Battery Multi-Charger Set keeps a fleet of Cisco 7926G/7925G/7925G-EX Unified Wireless IP Phone battery packs charged for continuous, round-the-clock use. Charges up to NINE (9) standard or extended Li-Ion battery packs and can be placed on a desk or mounted on the wall.

- The ONLY Battery Multi-Charger for Cisco 7926G/7925G/7925G-EX Unified Wireless IP Phone battery packs in the market
- Complete compliance with environment and safety standards
- Charge up to nine (9) zBattery and Cisco 7926G/7925G Unified Wireless IP Phone standard or extended battery packs at the same time
- It is part of zCover Unified Power Solutions which allows you expand or exchange modules with same or different models to meet your need.
- Separate LEDs show charge and ready states for each battery slot
- Switches to a trickle charge when battery is full
- Safety first, intelligent battery temperature monitoring discontinues charge when battery temperature is over 113°F (45°C)
- Can be placed on a desk or mounted on the wall to save space(Wall mount kits sale separately).
- Power supply has switchable power cord for different countries
- Compatible with zBattery U8ZBAE12 Li-ion batteries for zCover Bluetooth Desktop Speaker Phone for zBattery and Cisco 7926G/7925G Unified Wireless IP Phone.

Fits zBattery and Cisco 7926G/7925G Wireless IP Phone Batteries

Compatible with zBattery and Cisco Unified Wireless IP Phone 7926G/7925G standard and extended battery packs

Independent “smart” charger circuit in each slot

The zAdapter® CI925U3B Battery Multi-Charger can be placed on a desktop or mounted on the wall

Product ID:CI925U3B| Compatibility: zBattery and Cisco 7926G/7925G/7925G-EX Wireless IP Phone Battery

Specifications	
Dimensions (H x W x D)	5.6in x 7.0in x 13.2in 14.2cm x 17.8cm x 33.5cm
Weight	1134g; 2.5lb
Power Supply	INPUT : AC100-240V 50/60Hz 1.50A OUTPUT: DC5.0V 6000mA (each battery slot approximately 600mA)
Operating Temperature	14°F to 131°F (-10°C to 55°C)
Storage Temperature	-22°F to 140°F (-30°C to 60°C)
Relative Humidity	10 to 95% (no condensing)
Drop Specification	2.5 ft (0.75m) to concrete
Charging Time	Use zAdapter power supply: 2.5 hours / 3 hours (standard battery pack / extended battery pack)
What in the box:	1 x zAdapter® CI925U3B Battery Multi-Charger 1 x zAdapter® AC power supply and AC power cord

Part ID Number	Description
CI925U3B	Unified Battery Charger 3 Bay Rack Set (with AC adapter) for zBattery and Cisco 7926G, 7925G/7925G-EX Wireless IP Phone Batteries
ZDAD120A	zAdapter® AD120A power supply for Battery Multi-Charger with AC power cord,
ZDADAT-NA=	zAdapter® ZDACDCXA AC Power Cord, North America
ZDADAT-AU=	zAdapter® ZDACDCXA AC Power Cord, Australia
ZDADAT-JP=	zAdapter® ZDACDCXA AC Power Cord, Japan
ZDADAT-UK=	zAdapter® ZDACDCXA AC Power Cord, United Kingdom
ZDADAT-EU=	zAdapter® ZDACDCXA AC Power Cord, Continental Europe
ZDADAT-CN=	zAdapter® ZDACDCXA AC Power Cord, China

Related zCover Products

zBattery

Bluetooth Speaker Phone

Multi-Charger

Bluetooth Speaker Phone with Desktop Dual Charger

Ruggedized Silicone Case

Tech-Leather Carrying Case

Holster Carry Case

zCover, Inc.
Tel: (604)273-3003 Fax: (604)273-3023
PO & Sales Support: sales@zcover.com
100-13551 Verdun Place Richmond, BC,
Canada V6V 1W5
Purchase Online: www.zcover.com

©2011 zCover Inc. All rights reserved. zCover, zBattery and zAdapter are registered trademarks in USA and other countries.
All other trademarks are the property of their respective owners.